

Spheerol™ BNS 2

High temperature bearing grease

Description

Castrol Spheerol™ BNS 2 is a non melting grease for the lubrication of plain and roller bearings at high temperatures. It has no drop point. This grease is based on an oxidation resistant, thermally stable base oil and an inorganic thickener.

Application

Spheerol BNS 2 is suitable for the lubrication of bearings at high temperatures, such as soot blower bearings, in carriages for hardening, drying in tunnel ovens, also in bearings of bitumen mixing plants, cranes in foundries, etc.

Spheerol BNS 2 can be used at a temperature range of -20°C to +150°C, and for short periods at a temperature range of up to +220°C. Frequent re-greasing or grease change should be considered subject to application requirements.

Advantages

- High oxidation stability.
- Wide range temperature of application.
- Easy to dispense.
- Good protection against corrosion.
- Reduces mechanical wear.

Additional Information

In order to minimise potential incompatibilities when converting to a new grease, all previous lubricant should be removed as much as possible prior to operation. During initial operation, re-lubrication intervals should be closely monitored to ensure all previous lubricant is purged.

Typical Characteristics

Name	Method	Units	Spheerol BNS 2
Thickener			Bentone
NLGI Class	ISO 2137	-	2
Texture	Visual		Smooth
Colour	Visual	-	Brown
Dropping Point, Grease	IP 396	°C	300 min
Base oil kinematic viscosity at 40°C	ASTM D445	mm ² /s	180- 220
Worked penetration at 25°C after 60 strokes	ASTM D217	0,1 mm	265 - 295
Working stability 60 / 100,000 strokes @ 25°C	ASTM D217	0.1 mm	60 max
Oil separation 168 hr / 40°C	IP 121	% wt	5 max
Anti-Rust Performance (Emcor)	IP220	rating	0/0 max
Oxidation Stability, 100 hr / 100°C	ASTM D942	bar	0.4 max
Copper Corrosion, 24 hours @ 100°C	ASTM D4048	rating	1b max
Water Resistance, 3 hr / 90°C	ASTM D1264 / DIN 51 807/1	rating	1-90 max
4 ball weld point	DIN 51806	kg	200 min
Flow pressure @ -20°C	DIN 51805	hPa	<1400 @ -20 °C

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Storage

Supplied in packs of approximately 18 kg pails and 180 kg drums. Note the actual pack size may vary according to country of supply.

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Spheerol™ BNS 2

06 Oct 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Marine, Technology Centre, Whitchurch Hill, Pangbourne, Reading RG8 7QR, United Kingdom

www.castrol.com/marine